

[0008] The photodetector 108 generally employs a quadrant photodetector, which is divided into four elements 121 by a separation area 122 as shown in Fig. 4. The method for detecting a position using a photodetector has been described in e.g., Japanese Laid-open patent 2001-94513. Such a photodetector 108 is arranged so that the light receiving surface (plate) of the quadrant photodetector is generally located in a position defocused to a converging point of the lens group 109.

Please amend paragraphs [0027] through [0028] as follows:

~~[0033]~~ ^[0027] Fig. 1 is a schematic drawing showing an optical transmission device (device X ~~M~~) for providing stable communication with a device Y ~~N~~ (not shown) according to a first embodiment of the present invention. A laser beam, which is emitted from a laser diode 1, is propagated as linearly polarized light and is transmitted through a lens group 2 (with positive power). The beam is reflected from a boundary surface of a polarizing beam splitter 3, and is reflected by a variable-angle mirror 4a of an optical-axis adjusting unit 4. It is then projected as transmitting light LA from device X ~~M~~ to device Y ~~N~~.
~~[0034]~~ ^[0028] A received light beam LB is transmitted from the device Y ~~N~~ and is reflected by the variable-angle mirror 4a about an optical axis 12, and transmitted through the beam splitter 3 to a received light branching element 5. A substantial portion (LBa) of the received light beam LB is transmitted through the beam branching element 5, and is converged onto a photodetector 6 by a lens group 7. The photodetector 6 acts as a real signal photodetector. The other portion of light beam LBb reflected from the beam branching element 5 is converged by a lens group 9 as a luminous flux through a cross pattern filter 13 for receipt by a photodetector 8. Thereafter, signals generated by photodetector 8 are received and processed by a signal processing unit 10, which are then transmitted to a mirror drive control unit 11 to generate a correction signal.

[Signature]
2-14
2008

[Signature]
2-14
2008